

FORCE/3

3.0 & 4.0 DP Models

THE FORCE/3 Insulation Blowing Machine



HIGHER PRODUCTION

NEW
4.0 DP

The Force/3, the machine that defined portable insulation blowers, has now been upgraded for newer, more demanding applications. The new **FORCE/3 4.0DP** is powered by two 7.2" blowers, boasting 232 CFM with a pressure of 4.0 PSI at the outlet. Portable and lightweight at just 350 lbs and with 10" poly wheels, this machine is more nimble than any other machine in its class. Because of Intec's state-of-the-art blower control and powerful 4.0 blowers, the Force/3 is a real heavyweight contender. Attic, dense-pak and wall spray are just a few of the applications that this machine can do, and with ease.

For less demanding jobs, The **FORCE/3 3.0** is still the same reliable workhorse that set the standards since 1978. With its dual 5.7" blower system, the Force/3 3.0 delivers over 250 CFM at 3.0 PSI. Both Force/3's have large 12" x 14" steel airlock, cast urethane seals and direct drive transmission, which make them more powerful and portable than any of its rivals. Powerful, lightweight and energy efficient is what makes this mid size machine the choice of insulation contractors anywhere.

RELIABLE WORKHORSE

Choose the FORCE/3 for it's high production on cellulose, Fiberglass and Rockwool insulation materials. With either model the Force/3 has been designed to blow over a ton of material an hour. The new 4.0 DP model can easily do Dense Pack sidewalls with the enhanced performance from the larger 4.0 blowers. The agitation system is still the same durable design using a five blade agitator and the trouble free direct drive 1-1/2 hp motor system.



SIMPLE TO OPERATE

Applicators choose the Force/3 for its versatility, high production and convertibility. Not only is the Force/3 easy to operate, but with a mere two adjustments the Force/3 becomes a precision sidewall and spray wall machine. With the Five-blade vertical agitation system the Force/3 can handle up to a 50/50 blend of wet to dry material with extra horsepower to spare.



Five blade
Agitator
System

SPECIFICATIONS



Height 51"



Width 30"

Length 53"

Height	51"
Width	30"
Length	53"
Weight	3.0 335 lbs, 4.0 DP 350 lbs
Hopper Capacity	70 lbs.
Hose size	3"
Blower (s)	5.7 diameter... (2).....x 128 cfm = 256 @ 3.0 PSI 7.2 diameter.. (2)..... x 116 cfm = input 232 CFM @ 4.0 PSI
Agitator Mtr.	1-1/2 hp TEFC
Transmission	Worm gear / direct drive
Airlock	12 x 14 steel, optional stainless inserts
Electric	115V/220V 50/60Hz
Power requirements	Two 20 amp circuits@115V
Agitator	5-blade vertical
Warranty	One year limited; 90 days, electric, airlock system and blower.

THE FORCE/3 Insulation Blowing Machine



ATTIC

*The finest portable
insulation machine in its class, just see why!*



SIDEWALL

FIBERGLASS

Production up to 45 bags per hour*

CELLULOSE

Production up to 115 bags per hour*



**SPRAY-ON/
SPRAYWALL**



ALL FORCE/3'S COME WITH:

- 100 feet of 3" hose
- (2) 100' power cords
- variable speed blower control
- 100' remote control cord
- (1) 3" hose connector
- (3) 3" hose clamps

OPTIONS AVAILABLE:

- Hopper extension
- Stainless steel airlock inserts
- Wireless remote

All these great features are wrapped up into one machine. That's what you will get when you purchase a FORCE/3; high production, portable, lightweight, reliable, and Intec quality!

PRODUCTION SPECIFICATIONS

* Based on 100' of 3" hose @ two story lift.

Cellulose, light density	3600 Sq Ft of R-19 per hour	2520 lbs/hr
Fiberglass, Certainteed, IS IV	2700 Sq Ft of R-19 per hour	780 lbs/hr
Fiberglass, Guardian, Pro White III	3400 Sq Ft of R-19 per hour	1350 lbs/hr
Fiberglass, JM, Climate Pro	3200 Sq Ft of R-19 per hour	1000 lbs/hr
Fiberglass, OC, Pro Pink	3700 Sq Ft of R-19 per hour	1170 lbs/hr

MANUFACTURED BY:



Phone 800-666-1611
Local 303-833-6644
Fax 303-833-6650
www.inteccorp.com
info@inteccorp.com

3771 Monarch Street • Frederick, CO 80530