



## Insulation Blowing Machine



# WASP



*Take the sting out of purchasing your next insulation blower...*

### Return On Investment

Retailers and contractors will increase their profit generating opportunities with the Wasp's versatility and greater up time compared to the competition. Lower operating costs, less maintenance, ease of transportation, and reduced fuel consumption gives you the competitive edge.



### Greater Production

Insulate an average attic in less than one hour with Cellulose (over 75 bags per hour) or Fiberglass (over 18 bags per hour), in addition the Wasp can also handle Stonewool, Vermiculite, Perlite, and most other loose fill materials.

### Multiple Applications

The Wasp can handle the most demanding applications, open attic, drill & fill, wall spray, spray-on and any other job you ask it to do.

### Portability

With the built in handles and 10" wheels, this machine is easy to move around on the job site which allows you to get to those hard to reach places and only weighs 280 lbs.

*...by having greater versatility, greater production and higher return on investment, nothing comes close to a Wasp!*

## COMES STANDARD WITH

## PRODUCTION



- Wheels & handles to ease portability
- Emergency stop button
- 100' remote control cord
- Material slide gate
- Polyurethane airlock seals
- (2) 50'x3" blowing hose
- (1) 3" Steel hose connector
- (3) 3" Stainless steel hose clamps
- (2) 100' 10/3 Twist lock cords
- Blower variable speed control
- Stainless steel airlock inserts



**Cellulose Production**  
1750 lbs per hour



**Fiberglass Production**  
475 lbs per hour

**It takes less than one hour to install  
R-30 in a 1000 square foot attic.**

## Specifications



Dimensions	31-3/8"W x 33"L x 44"H
Weight (machine only)	280 lbs
Weight (shipping)	327 lbs
Production	1750 lbs/hr- Cellulose 475 lbs/hr- Fiberglass 1115 lbs/hr- Rockwool (Stonewool) 3"
Hose Outlet Size	18/4 x 100' std 150' (opt)
Remote Cord	11 cu. ft.
Hopper Capacity	1.5 HP - 14.5 FLA.
Drive motor	Custom, Direct drive
Transmission	12" Steel
Airlock	2 stage, 2 x 8.5 amp = 17 amp
Blowers	2 x 101 cfm = 202 cfm
*Electrical	115 VAC / 60 Hz
Power cord	(2) 10/3 x 100' Twist lock
Warranty	1 year limited; 90 days electric, airlock system and blower

\* 230 VAC / 50 Hz available upon Request

## Electrical Features



- Main control switches
- Blower fuses
- Emergency stop button
- Blower variable speed control
- Agitator circuit breaker
- Remote cord
- Twist lock plugs

## Blower Features



- 5.7" Diameter
- Dual blower 202 cfm
- 3.4 psi
- 2 stage

## Applications

- Attics
- Spray-in
- Drill & Fill
- Spray-on

## Accessories



Pressure Gauge



Contractor Kit



Hose Fittings



Wet Spray Nozzles



Hose Swivels

## Distributed By



## Manufactured By



1-800-666-1611

P.O. Box 579  
3771 Monarch Street  
Frederick, CO 80530 USA

Local: 303-833-6644  
Fax: 303-833-6650  
www.inteccorp.com

*The Intec Pledge*

*Provide the finest equipment in the industry while continuing to strive for 100% satisfaction.*