www.actoolsupply.com

Tru Pointe® 2100 Features & Benefits

- Capable of detecting a 5 PSI leak out of a 0.005" hole, 30 to 40 feet away (depending on background noise).
- Capable of detecting ANY gas leaks, regardless of chemical property or concentration.
- Ideal for steam trap testing, detecting bearing wear, gas and valve leaks.
- Unaffected by wind or temperature fluctuations, other sounds or gases in the test area.
- Kit includes the Tru Pointe® 2100, high-quality noise attenuating headphones, 6" Touch Probe, segmented 3' extension Touch Probe, 6" Wave Guide– packed in a hard plastic carrying case.
- Unique AudioZoom™ volume control.

Tru Pointe® 2100 Specifications

Mechanical:	
Dimensions:	8.185" (20.78cm) X 2.4" (61mm) X .875" (22.22mm)
Weight:	0.5lb (233gr) Includes Battery
Body Materials:	Aluminum and ABS
Audio Connector:	3.5mm Stereo
Electrical:	
Airborne Sensor Sensitivity:	-80db/V-μbar
Ultrasound Converter Type:	Digitally Controlled Heterodyne
Frequency response, Airborne, High:	AirHi: 34kHz to 42kHz
Frequency response, Airborne, Low:	AirLow: 26kHz to 34kHz
Frequency response, Touch Probe High:	PbHi: 34kHz to 42kHz
Frequency response, Touch Probe, Low:	PbLo 16kHz to 24kHz
Frequency response, Touch Probe, Sonic:	PbS: 0 to 10kHz
Controls:	4 Buttons (w/ Audio Zoom ™)
Output, Audio:	0Hz to 4kHz
Output, Visual:	20 Segment Bar Graph with Peak-Hold and Separate Alphanumeric Digital Display
Signal Output:	Heterodyne
ON Indicator:	Digital Display
Battery Type:	9 Volt
Run Time:	55-80 hrs

AC TOOL SUPPLY.COM
877-207-1244
aikencolon.com

When combined with the ultrasonic sound generator, the SoundBlaster®, the Tru Pointe® 2100 can detect leaks from tanks, enclosures, building doors & windows, automobile windows & windshields, walk-in coolers, clean rooms ship hatches and compartments.

Tru Pointe® 2100 Ultrasonic Leak Detector

Ordering Information	
28-8003	Tru Pointe® 2100 Ultrasonic Leak Detector Kit
28-8013	Tru Pointe® 2100 Ultrasonic Leak Detector Kit w/SoundBlaster®

Distributed By:

BACHARACH
The Measurable Difference

www.actoolsupply.com

TÜV ISO 9001:2008