



DC Power Port to Charge Cell Phones and Other Accessories

AL4CUBE BP

DC TO DC Power Cable LP-PC-DE

115 VAC Power Cable C7-PC-USA

Power Source Features

Internal Battery and Charger

- 12 VDC, 22amp/hr, deep cycle sealed lead acid, AGM battery
- Maintenance-free, non-spillable, and operates in any position
- Safely stored/operated at -40°F to 140°F, (-40°C to 60°C)
- 6 hour minimum recharge time. 12 hours or overnight to condition the battery from full discharge
- Rated for 500+ discharge cycles, 3 -5 year service life
- One year replacement warranty on battery pack and charger
- 3 amp Internal charger rated 50/60 hz, 110-240 VAC
- Supplied with charge cord and power port cable



DC to DC power cord and 115 VAC charger cables provided

12 volt DC power port can operate / charge accessory equipment like cell phones or laptops



Battery can be charged from a direct connection from a vehicle's battery system via jumper cables to battery posts located on the standard battery pack

[Air Systems AL2C-IR850 Air Light System ALS DC LED Lighting](#)

[Air Systems AL2C-IR940 Air Light System ALS DC LED Lighting](#)

[Air Systems AL2CUBEBP Air Light System ALS DC Portable LED Lighting](#)

[Air Systems AL4C-IR850 Air Light System ALS DC LED Lighting](#)

[Air Systems AL4C-IR940 Air Light System ALS DC LED Lighting](#)