

PRODUCT SPECIFICATIONS

60' Controlled Descent Device Kit

#5030

Features

- Controls descent at a constant Speed of 4-1/2' per second.
- Bi-Directional deceleration mechanism allows for evacuation of multiple users in rapid succession.
- Easily attaches to the back D-ring of a full body harness with a double-locking carabiner.

Material Specifications

- Webbing:** *Dyneema; Min. 4,000 lbs. tensile strength*
- Connectors:** *Alloy Steel; Min. 5,000 lbs. tensile strength*
- Connector Gates:** *Alloy Steel; Min. 3,600 lbs lbs. front and side load.*

Performance Specifications

- Tensile Strength:** *Min. 3,000 lbs.*
- Max. Capacity:** *310 lbs.*
- Max. Freefall:** *N/A*
- Average Arrest Force:** *N/A*
- Max. Elongation:** *N/A*

Relevant Standards

- OSHA:** *CFR1926.502, CFR1910.66*
- ANSI:** *A10.32-2004*
Z359.4-2009

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Not for fall arrest - see user instructions.

Falltech 5030 100 Rescue Device
Falltech 5030 60 Rescue Device



**AC TOOL
SUPPLY.COM**
877-207-1244

aikencolon.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.