

## Gillette GPE-95EV 9500 Watt Portable Gas Generator

### **MODEL GPE-95EV**

**60 HERTZ**

**Heavy Duty, long lasting portable power** for contractor and rental use. If you want clean, dependable emergency electric power, with the most reliable engines, then **GEN-PRO** is the right choice for you. These generator sets driven by **EPA Certified** engines and fuel systems, are made for the tough jobs when you need the reliability, and good clean electrical energy. This is exactly what you get, when you choose **GEN-PRO**, because of it's many heavy duty & exclusive features.



GENERATOR MODEL	GPE-95EV
MAX. KW @ 1 PH.	9.5
PRIME KW @ 1 PH.	8.5
PRIME AMPS @ 120 V.	70
PRIME AMPS @ 240 V.	35
GENERATOR REGULATION	5 % VOLTAGE REGULATION ON SINGLE PHASE GEN-SETS.
FREQUENCY REGULATION	5 %, (3 HERTZ) FREQUENCY REGULATION FROM NAME PLATE RATING
"KLEEN-POWER"™	ELECTRICAL WAVEFORM DISTORTION IS LIMITED TO JUST 6 % ON ALL GEN- PRO GEN-SETS
ENGINE MODEL (WARRANTY)	<b>VANGUARD / BRIGGS 479</b> V-TWIN O.H.V. (3 YEARS)
ENGINE START METHOD	12VDC ELECTRIC ONLY
ENGINE HP @ 3600 RPM	16 HP
ENGINE DISPLACEMENT	2 CYLINDER, 29.23 CU. IN. (479 CC)
ENGINE AIR CLEANER	HEAVY DUTY, LOW PROFILE, DUAL ELEMENT FILTERS
ENGINE FUEL TANK	7 GAL. (26.5 L.) METAL FUEL TANK WITH GAUGE, TWIST-CAP, & SLOSH VALVE
ENGINE OIL SYSTEM	FULL PRESSURE W/ SPIN ON OIL FILTER
LOW OIL PROTECTION	AUTOMATIC ENGINE SHUTDOWN PROTECTION AT LOW OIL LEVEL
db(A) AT 7 METERS	80
3/4 LOAD RUN TIME (HRS)	8.0
FUEL USE, GAL/LTR/HR	0.87 / 3.29
MOTOR START POWER	3 HP, CODE G ELECTRIC MOTOR
CRANE PICK-UP HOOK	OPTIONAL EQUIPMENT : CENTRAL PICK-UP ON TOP OF GEN-SET
2-WHEEL DOLLY KIT	OPTIONAL EQUIPMENT : COMPLETE WITH (2) HANDLES AND "NEVER GO FLAT" WHEELS
MAINLINE CB	EXCLUSIVE GROUND FAULT CIRCUIT INTERRUPTION (GFCI) ON 120 V. RECEPTACLES AND NOW INCLUDING 240 V. RECEPTACLES, PROVIDING A COMPLETE OPERATOR SHOCK PROOF PROTECTION
HOUR METER	RUN TIME HOURS, PLUS (3) MAINTENANCE ALERTS: 25 HOUR CHANGE OIL, 25 HOUR CHANGE OIL FILTER, 25 HOUR SERVICE AIR FILTER
POWER RECEPTACLES	(4) NEMA 5-15R, (1) L5-30R 120 VOLTS, AND (1) 14-50R 240 VOLTS RECEPTACLES
PROTECTIVE ROLL FRAME	RUGGED 1-1/4" ROUND ROLL FRAME, PROTECTING ENTIRE GEN-SET
LENGTH, INCHES	38
WIDTH, INCHES	26
HEIGHT, INCHES	28
SHIP WEIGHT, LBS.	280
CU. FEET SHIP BOX	20