

Schaefer Direct Flow 36DF-50 Air Circulation Fan

Schaefer Direct Flow 36DF-3 Air Circulation Fan

Schaefer Direct Flow 36DF Air Circulation Fan

36" Versa-Kool® Oscillating Wall Mount and Chain Mount Fans



VKC36




VS36VKWO-M-B

Reduce heat stress and improve air quality with Schaefer's 36" Oscillating or Chain Mounted Circulation Fans. Designed for high airflow and high efficiency, these versatile and durable fans are the ideal cooling solution for any industrial or commercial facility.

- Deep guard design provides unmatched performance at tremendously quiet noise levels. Rated up to 11,700 CFM!
- High density polyethylene housing has superior corrosion and moisture resistance, wide temperature range capability and high stress crack, wear and abrasion resistance.
- High quality totally enclosed motors and blades achieve maximum performance & efficiency.
- Oscillating Wall Mount Fan oscillates 90 degrees for cooling larger areas.
- Chain Mount Fan is designed for easy chain mount installation.
- Mistig kits available for even greater cooling!

| White Model | Black Model | Diameter | Phase | Mount | Cord | HP | Volts | Amps | Thrust (lbf) | CFM | RPM | Weight | Tested |
|-------------|--------------|----------|-------|-------|------|-----|---------|---------|--------------|--------|-----|--------|----------|
| VKC36 | VKC36-B | 36" | 1 | N | N | 1/2 | 115/230 | 7.0/3.5 | 5.74 | 11,693 | 825 | 71 | BESS LAB |
| VKC36-3 | VKC36-B-3 | 36" | 3 | N | N | 1/2 | 230/460 | 2.3/1.2 | 5.74 | 11,693 | 825 | 71 | SCHAEFER |
| VS36VKWO-M | VS36VKWO-M-B | 36" | 1 | Y | Y | 1/2 | 115/230 | 7.0/3.5 | 5.74 | 11,693 | 825 | 130 | BESS LAB |

36" & 42" Versa-Kool® Yoke Mount Circulation Fans



VK36

These durable and aesthetically pleasing fans feature a high airflow with a wide airflow pattern, which reduces the number of fans needed for complete coverage. The industry standard VK36 is joined by the VK42, with 25% greater airflow, for 2014.


- Powerful ½ HP motor provides high airflow with a wide airflow pattern for excellent coverage.
- High density polyethylene housing has superior impact resistance, wide temperature range capability and high crack, wear and abrasion resistance.
- Wide spacing steel guards are zinc dipped and powder coated for superior corrosion resistance.
- Thermally protected TEAO motor with matching blade delivers high performance and long life.
- Wide spacing, deep housing design enhances performance without sacrificing safety. OSHA compliant guards also available.
- Fans ship fully assembled, complete with 19" T-shaped, powder coated steel, fan mount.

| Model | Diameter | Phase | Mount | Cord | HP | Volts | Amps | Thrust (lbf) | CFM | RPM | Weight | Tested |
|--------|----------|-------|-------|------|-----|---------|---------|--------------|--------|-----|--------|----------|
| VK36 | 36" | 1 | Y | N | 1/2 | 115/230 | 7.0/3.5 | 5.83 | 11,399 | 825 | 70 | BESS LAB |
| VK36-3 | 36" | 3 | Y | N | 1/2 | 230/460 | 2.3/1.2 | 5.82 | 11,384 | 825 | 70 | BESS LAB |
| VK42 | 42" | 1 | Y | N | 1/2 | 115/230 | 7.0/3.5 | 7.2 | 14,866 | 825 | 75 | BESS LAB |
| VK42-3 | 42" | 3 | Y | N | 1/2 | 230/460 | 2.3/1.2 | 6.3 | 13,970 | 825 | 75 | BESS LAB |

Best Seller!

NEW!
Coming
Fall 2013

36" Direct Flow Basket Fans



36DF

This is Schaefer's most popular 36" agriculture circulation fan. This fan features very high airflow with a narrow airflow pattern to deliver high volumes of fast moving air to cool cows and other animals.

- Powerful ½ HP motor provides high airflow with a narrow airflow pattern for very high air speeds and effective cooling.
- Thermally protected TEAO motor with matching blade delivers high performance and long life.
- Safety spaced steel guards are zinc dipped and powder coated for superior corrosion resistance.
- Guards open easily for easy cleaning and/or blade replacement.
- Fan ships fully assembled, complete with 19" T-shaped, powder coated steel, fan mount.
- Available unassembled also, for high packing density and low shipping cost for international and other high volume orders.

| Model | Diameter | Phase | Mount | Cord | HP | Volts | Amps | Thrust (lbf) | CFM | RPM | Weight | Tested |
|--------|----------|-------|-------|------|-----|---------|---------|--------------|--------|-----|--------|----------|
| 36DF | 36" | 1 | Y | N | 1/2 | 115/230 | 7.0/3.5 | 7.90 | 13,041 | 825 | 70 | SCHAEFER |
| 36DF-3 | 36" | 3 | Y | N | 1/2 | 230/460 | 2.3/1.2 | 8.03 | 12,128 | 825 | 70 | SCHAEFER |

Best Seller!

Mount models without OSHA guards seven feet or higher.